


Quad 2-Input Data Selector/ Multiplexer with 3-State Outputs

This device selects a 4-bit nibble from either A or B inputs as determined by the Select input. The nibble is presented at the outputs in noninverted form when the Output Enable pin is at a low level. A high level on the Output Enable pin switches the outputs into the high-impedance state. The HC257 is similar in function to the HC157 which does not have 3-state outputs.

- Output Drive Capability: 15 LSTTL Loads
- Outputs Directly Interface to CMOS, NMOS, and TTL
- Operating Voltage Range: 2 to 6 V for HC device
- Low Input Current: 1 μ A
- DC, AC parameters guaranteed from -55°C to 125°C


DV74HC257
DV74HCT257



N Suffix
Plastic DIP
AVG-003 Case



D Suffix
Plastic SOP
AVG-004 Case



PIN ASSIGNMENT

Select	1	●	16	V _{CC}
A0	2		15	Output Enable
B0	3		14	A3
Y0	4		13	B3
A1	5		12	Y3
B1	6		11	A2
Y1	7		10	B2
GND	8		9	Y2

TRUTH TABLE

Inputs		Outputs
Output Enable	Select	Y0-Y3
H	X	Z
L	L	A0-A3
L	H	B0-B3

H = High Logic Level
L = Low Logic Level
A0-A3, B0-B3 = the levels of the respective Nibble Inputs
Z=High Impedance
X = Don't Care

ABSOLUTE MAXIMUM RATINGS

Maximum ratings are those values beyond which damage to the device may occur.

Symbol	Parameter	Value	Unit
V _{CC}	DC Supply Voltage (Referenced to GND)	-0.5 to +7.0	V
V _{IN}	DC Input Voltage (Referenced to GND)	-1.5 to V _{CC} +1.5	V
V _{OUT}	DC Output Voltage (Referenced to GND)	-0.5 to V _{CC} +0.5	V
I _{IN}	DC Input Current, per Pin	± 20	mA
I _{OUT}	DC Output Current, per Pin	± 35	mA
I _{CC}	DC Supply Current, V _{CC} and GND Pins	± 75	mA
P _D	Power Dissipation in Still Air, Plastic DIP SOP Package	750 500	mW
T _{STG}	Storage Temperature Range	-65 to +150	°C
T _L	Lead Temperature, 1mm from Case for 10 Seconds	260	°C

GUARANTEED OPERATING CONDITIONS

Symbol	Parameter	Min	Max	Unit
V _{CC}	DC Supply Voltage HC(HCT), Referenced to GND	2.0(4.5)	6.0(5.5)	V
V _{IN} , V _{OUT}	DC Input Voltage, Output Voltage ,Referenced to GND	0	V _{CC}	V
T _A	Ambient Temperature	-55	+125	°C
t _r , t _f	Input Rise and Fall Time: HC: V _{CC} =2.0V HCT: V _{CC} =5.5V / HC: V _{CC} =4.5V HC: V _{CC} =6.0V	0 0 0	1000 500 400	ns

DC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Conditions	V _{CC} V	Guaranteed Limits			Unit
				25°C to -55°C	≤85°C	≤125°C	
V _{IH}	Minimum High-Level Input Voltage	I _{OUT} ≤20μA	2.0 4.5 6.0	1.5 3.15 4.2	1.5 3.15 4.2	1.5 3.15 4.2	V
V _{IL}	Maximum Low- Level Input Voltage	I _{OUT} ≤20μA	2.0 4.5 6.0	0.3 0.9 1.2	0.3 0.9 1.2	0.3 0.9 1.2	V
V _{OH}	Minimum High-Level Output Voltage	V _{IN} = V _{IH} or V _{IL} I _{OUT} ≤ 20 μA	2.0 4.5 6.0	1.9 4.4 5.9	1.9 4.4 5.9	1.9 4.4 5.9	V
		V _{IN} = V _{IH} or V _{IL} , I _{OUT} ≤6.0mA I _{OUT} ≤ 7.8 mA	4.5 6.0	3.98 5.48	3.84 5.34	3.7 5.2	
V _{OL}	Maximum Low Level Output Voltage	V _{IN} = V _{IH} or V _{IL} I _{OUT} ≤ 20 μA	2.0 4.5 6.0	0.1 0.1 0.1	0.1 0.1 0.1	0.1 0.1 0.1	V
		V _{IN} = V _{IH} or V _{IL} , I _{OUT} ≤ 6.0mA I _{OUT} ≤ 7.8 mA	4.5 6.0	0.26 0.26	0.33 0.33	0.40 0.40	V
I _{IN}	Maximum Input Leakage Current	V _{IN} = V _{CC} or GND	6.0	±0.1	±1.0	±1.0	μA
I _{OZ}	Maximum Three-State Leakage Current	Output in High-Impedance State V _{in} =V _{IL} or V _{IH} V _{out} =V _{CC} or GND	6.0	±0.5	±5.0	±10.0	μA
I _{CC}	Maximum Quiescent Supply Current (Per Package)	V _{IN} = V _{CC} or GND I _{OUT} =0 μA	6.0	8.0	80	160	μA

AC ELECTRICAL CHARACTERISTICS over full operating conditions(C_L=50pF, Input t_f=t_r=6ns)

Symbol	Parameter	V _{CC} V	Guaranteed Limit			Unit
			25°C to -55°C	≤85°C	≤125°C	
t _{PLH} , t _{PHL}	Maximum Propagation Delay Time, Nibble A or B to Output Y	2.0 4.5 6.0	100 20 17	125 25 21	150 30 26	ns
t _{PLH} , t _{PHL}	Maximum Propagation Delay Time, Select to Output Y	2.0 4.5 6.0	100 20 17	125 25 21	150 30 26	ns
t _{PLZ} , t _{PHZ}	Maximum Propagation Delay Time, Output Disable to Output Y	2.0 4.5 6.0	150 30 26	190 38 33	225 45 38	ns
t _{PZL} , t _{PZH}	Maximum Propagation Delay Time, Output Enable to Output Y	2.0 4.5 6.0	150 30 26	190 38 33	225 45 38	ns
t _{TLH} , t _{THL}	Maximum Output Transition Time Any Output	2.0 4.5 6.0	60 12 10	75 15 13	90 18 15	ns
C _{IN}	Maximum Input Capacitance	—	10	10	10	pF
C _{OUT}	Maximum Three-State Output Capacitance (Output High-Impedance)	—	15	15	15	pF

C _{PD}	Power Dissipation Capacitance (Per Multiplexer) Used to determine the no-load dynamic power consumption, $P_D = C_{PD} V_{CC}^2 f + I_{CC} V_{CC}$	Typical @ 25°C, V _{CC} = 5 V	pF
		39	

DC ELECTRICAL CHARACTERISTICS



Symbol	Parameter	Conditions	V _{CC} (V)	Guaranteed Limits			Unit
				25°C to -55°C	≤ 85°C	≤ 125°C	
V _{IH}	Minimum High Level Input Voltage	V _{OUT} = V _{CC} - 0.1 V I _{OUT} ≤ 20 μA	4.5 5.5	2.0 2.0	2.0 2.0	2.0 2.0	V
V _{IL}	Maximum Low Level Input Voltage	V _{OUT} = 0.1V or V _{CC} - 0.1 V I _{OUT} ≤ 20 μA	4.5 5.5	0.8 0.8	0.8 0.8	0.8 0.8	V
V _{OH}	Minimum High Level Output Voltage	V _{IN} = V _{IH} I _{OUT} ≤ 20 μA	4.5 5.5	4.4 5.4	4.4 5.4	4.4 5.4	V
		V _{IN} = V _{IH} I _{OUT} ≤ 6.0 mA	4.5	3.98	3.84	3.70	V
V _{OL}	Maximum Low Level Output Voltage	V _{IN} = V _{IL} I _{OUT} ≤ 20 μA	4.5 5.5	0.1 0.1	0.1 0.1	0.1 0.1	V
		V _{IN} = V _{IL} I _{OUT} ≤ 6.0 mA	4.5	0.26	0.33	0.40	V
I _{IN}	Maximum Input Leakage Current	V _{IN} =V _{CC} or GND, Pins 1 or 19	5.5	±0.1	±1.0	±1.0	μA
I _{OZ}	Maximum 3-State Current (Output in High Impedance State)	V _{IN} =V _{IL} or V _{IH} V _{OUT} =V _{CC} or GND, I/O Pins	5.5	±0.5	±5.0	±10.0	mA
I _{CC}	Maximum Quiescent Supply Current	V _{IN} = V _{CC} or GND I _{OUT} = 0 μA	6.0	4	40	160	μA
ΔI _{CC}	Additional Quiescent Supply Current (per Package)	V _{IN} =2.4 V, Any One Input V _{IN} = V _{CC} or GND, Other Inputs I _{OUT} = 0 μA	5.5	-55°C to 25°C	25°C to 125°C	mA	
				2.9	2.4		

AC ELECTRICAL CHARACTERISTICS over full operating conditions (C_L=50pF, Input t_f=t_r=6ns)

Symbol	Parameter	V _{CC} V	Guaranteed Limit			Unit
			25°C to -55°C	≤ 85°C	≤ 125°C	
t _{PLH} , t _{PHL}	Maximum Propogation Delay Time, Input D to Output Y or \bar{Y}	5.0 ±10%	37	46	56	ns
	Maximum Propogation Delay Time, Input A to Output Y or \bar{Y}		41	51	62	ns
	Maximum Propogation Delay Time, Output Enable to Output Y		39	49	59	ns
	Maximum Propogation Delay Time, Output Enable to Output \bar{Y}		29	36	44	ns
	Maximum Propogation Delay Time, Output Enable to Output \bar{Y}		44	55	66	ns
	Maximum Propogation Delay Time, Output Enable to Output \bar{Y}		30	38	45	ns
	Maximum Output Transition Time Any Output		15	19	22	ns
C _{IN}	Maximum Input Capacitance	—	10	10	10	pF
C _{OUT}	Maximum Three-State Output Capacitence (Output High-Impedance)	—	15	15	15	pF

CPD	Power Dissipation Capacitance (Per Package) Used to determine the no-load dynamic power consumption, $P_D = CPD V_{CC}^2 f + I_{CC} V_{CC}$	Typical @ 25°C, V _{CC} = 5 V			pF
		36			

SWITCHING WAVEFORMS



Input and Output Threshold Voltage: $V_T = 50\% V_{CC}$ for HC, 1.3V for HCT, $V_H = V_{CC}$ for HC, 3V for HCT