



8-1 Data Selector/Multiplexer with 3-State Outputs

The LS/ALS251 is a high speed 8-input multiplexer. It provides the ability to select one bit of data from up to 8 sources. Both assertion and negation outputs are provided. The outputs can be driven into a high impedance state.

- AVG's LS operates over extended V_{cc} from 4.5 to 5.5 V
- AVG's LS and ALS both have guaranteed DC and AC specification over full temperature and V_{cc} range
- Switching specifications for ALS at 50 pF
- AVG's ALS has the lowest speed power product (4pJ per gate typical) of all logic series

DV74LS251
DV74ALS251



PIN ASSIGNMENT

D3	1	●	16	V _{CC}
D2	2		15	D4
D1	3		14	D5
D0	4		13	D6
Y	5		12	D7
Y-bar	6		11	A0
Output Enable	7		10	A1
GND	8		9	A2

ABSOLUTE MAXIMUM RATINGS

Maximum ratings are those values beyond which damage to the device may occur.

Symbol	Parameter	LS251	ALS251	Unit
V _{CC}	Supply Voltage	7.0	7.0	V
V _{IN}	Input Voltage	7.0	7.0	V
T _{STG}	Storage Temperature Range	-65 to +150	-65 to + 150	°C
V _{OZ}	Output Voltage - High Impedance	5.5	5.5	V

GUARANTEED OPERATING CONDITIONS

Symbol	Parameter	LS251		ALS251		Unit
		Min	Max	Min	Max	
V _{CC}	Supply Voltage	4.5	5.5	4.5	5.5	V
V _{IH}	High Level Input Voltage	2.0		2.0		V
V _{IL}	Low Level Input Voltage		0.8		0.8	V
I _{OH}	High Level Output Current		-2.6		-2.6	mA
I _{OL}	Low Level Output Current		24		24	mA
T _A	Ambient Temperature Range	-10 to +70		-10 to +70		°C


DC ELECTRICAL CHARACTERISTICS over ambient temperature range

Symbol	Parameter	Conditions	LS251			ALS251			Unit
			Min	Typ	Max	Min	Typ	Max	
V_{IK}	Input Clamp Voltage	$V_{CC} = \text{min}, I_{IN} = -18 \text{ mA}$			-1.5			-1.5	V
V_{OH}	High Level Output Voltage	$V_{CC} = \text{min}, I_{OH} = -0.4 \text{ mA}$				2.5			V
		$V_{CC} = \text{min}, I_{OH} = -2.6 \text{ mA}$	2.4	3.1		2.4	3.2		
V_{OL}	Low Level Output Voltage	$V_{CC} = \text{min}; I_{OL} = 12 \text{ mA}$		0.25	0.4		0.25	0.4	V
		$V_{CC} = \text{min}; I_{OL} = 24 \text{ mA}$		0.35	0.5		0.35	0.5	V
I_{OZH}	Output Off Current HIGH	$V_{CC} = \text{max}, V_{IN} = 2.7 \text{ V}$			20			20	μA
I_{OZL}	Output Off Current LOW	$V_{CC} = \text{max}, V_{IN} = 0.4 \text{ V}$			-20			-20	μA
I_{IH}	High Level Input Current	$V_{CC} = \text{max}, V_{IN} = 2.7 \text{ V}$			20			20	μA
	High Level Input Current	$V_{CC} = \text{max}, V_{IN} = 7.0 \text{ V}$			0.1			0.1	mA
I_{IL}	Low Level Input Current	$V_{CC} = \text{max}, V_{IN} = 0.4 \text{ V}$			-0.4			-0.1	mA
I_o	Short Circuit Current	$V_{CC} = \text{max}, V_O = 2.25 \text{ V}$	-30	-130	-30			-112	mA
I_{CC}	Supply Current	$V_{CC} = \text{max}, V_E = 0 \text{ V}$			10		7	10	mA
		$V_{CC} = \text{max}, V_E = 4.5 \text{ V}$			12		9.4	14	

SWITCHING CHARACTERISTICS over full operating conditions

Symbol	Parameter	LS251 $C_L = 15 \text{ pF}$ $R_L = 2.0 \text{ k}\Omega$		ALS251 $C_L = 50 \text{ pF}$ $R_1 = R_2 = 500 \Omega$		Unit
		Min	Max	Min	Max	
t_{PLH}	Propagation Delay, Select to Y Output		33	5	18	ns
			33	8	24	
t_{PHL}	Propagation Delay, Select to Y Output		45	8	24	ns
			45	7	23	
t_{PLH}	Propagation Delay, Data to Y Output		15	2	10	ns
			15	3	15	
t_{PHL}	Propagation Delay, Data to Y Output		28	3	15	ns
			28	3	15	
t_{PZH}	Propagation Delay, Output Enable time to \bar{Y} Output		27	3	15	ns
			40	3	15	
t_{PZL}	Propagation Delay, Output Enable time to Y Output		45	3	15	ns
			40	3	15	
t_{PZH}	Propagation Delay, Output Disable time to \bar{Y} Output		55	2	10	ns
			25	1	10	
t_{PZL}	Propagation Delay, Output Disable time to Y Output		45	2	10	ns
			25	1	10	

SWITCHING WAVEFORMS



TRUTH TABLE

Output Enable	Address Inputs			Data Inputs								Data Outputs	
	A2	A1	A0	D0	D1	D2	D3	D4	D5	D6	D7	\bar{Y}	Y
H	X	X	X	X	X	X	X	X	X	X	X	Z	Z
L	L	L	L	L	X	X	X	X	X	X	X	H	L
L	L	L	L	H	X	X	X	X	X	X	X	L	H
L	L	L	H	X	L	X	X	X	X	X	X	H	L
L	L	L	H	X	H	X	X	X	X	X	X	L	H
L	L	H	L	X	X	L	X	X	X	X	X	H	L
L	L	H	L	X	X	H	X	X	X	X	X	L	H
L	L	H	H	X	X	X	L	X	X	X	X	H	L
L	L	H	H	X	X	X	H	X	X	X	X	L	H
L	H	L	L	X	X	X	X	L	X	X	X	H	L
L	H	L	L	X	X	X	X	H	X	X	X	L	H
L	H	L	H	X	X	X	X	X	L	X	X	H	L
L	H	H	L	X	X	X	X	X	X	L	X	H	L
L	H	H	L	X	X	X	X	X	X	H	X	L	H
L	H	H	H	X	X	X	X	X	X	X	L	H	L
L	H	H	H	X	X	X	X	X	X	X	H	L	H

H=High Logic Level

L=Low Level Logic

X=Don't Care

Z=High Impedance State