


PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24											
COM	COM	6E	6D	6C	DP6	5E	5D	5C	DP5	4E	4D	4C	DP4	3E	3D	3C	DP3	2E	2D	2C	DP2	1E	1D	1C	1B	1A	1F	1G	2B	2A	2F	2G	COL1	3B	3C
PIN	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48											
COM		DP3	2E	2D					2C	DP2	1E	1D	1C	1B	1A	1F	1G	2B	2A	2F	2G	COL1	3B	3C											
PIN	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70													
COM		3A	3F	3G					4B				4A	4F	4G	COL2	5B	5A	5F	5G	6B	6A	6F	6G	COM										

NOTES:

1. TOLERANCES UNLESS OTHERWISE SPECIFIED ± 0.20
2. VIEWING ANGLE: 12:00 O'CLOCK
3. DISPLAY MODE: POSITIVE, REFLECTIVE, TN TYPE
4. DUTY CYCLE: STATIC
5. DRIVING VOLTAGE: 5.0V
6. OPERATING TEMPERATURE: -30°C TO 85°C
7. STORAGE TEMPERATURE: -40°C TO 90°C



Revision Record		Date	AZ Displays, Inc.		
1	Viewing Angle: 6 o'clock to 12 o'clock	4/18/02	DRAWN BY: W.L.L	TITLE:	SCALE:
2			CHECKED BY: H.L.P		UNIT: mm
3			APP BY:	GD- 269P	SIZE: A4
4			DATE: 96.3.22	SHEET 1	OF 1