



# EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : CDLE-136-069 REV.: 2

10.0mm Round Type LED Lamps

PART NO. : 1363-2UYOC/S530-A4

ECN: \_\_\_\_\_ Page: 1/4

## ■ Features :

- Choice of various viewing angles
- Available on tape and reel.
- Reliable and robust



## ■ Descriptions :

- The series is specially designed for applications requiring higher brightness
- The led lamps are available with different colors, intensities,

## ■ Applications :

- TV set
- Monitor
- Telephone
- Computer

## ■ Package Dimensions:



## ■ Notes :

1. All dimensions are in millimeters.
2. An epoxy meniscus may extend about 1.5mm(0.059") down to the lead.
3. Tolerances unless Dimension  $\pm 0.25$ mm.

PART NO.	Chip		Lens Color
	Material	Emitted Color	
1363-2UYOC/S530-A4	AlGaInP	Yellow Orange	Water Clear

Office : 7C Building, Lian Hua Port Industrial District, Lian Hua Shan  
Bonded Pricessing Zone Pan Yu, Guang Zhou, China  
TEL. : (020)84860913,84860914  
FAX : (020)84860600  
[http : //www.everlight.com](http://www.everlight.com)



## 10.0mm Round Type LED Lamps

PART NO. : 1363-2UYOC/S530-A4 ECN:                      Page: 2/4

## ■ Absolute Maximum Ratings at Ta = 25°C

Parameter	Symbol	Rating	Unit
Forward Current	IF	25	mA
Operating Temperature	Topr	-40 to +85	°C
Storage Temperature	Tstg	-40 to +100	°C
Soldering Temperature	Tsol	260 ± 5	°C
Electrostatic Discharge	ESD	2000	V
Power Dissipation	Pd	60	mW
Peak Forward Current(Duty 1/10 @ 1KHz)	IF(Peak)	160	mA
Reverse Voltage	VR	5	V

## ■ Electronic Optical Characteristics :

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	Iv	1000	2500	/	mcd	IF= 20 mA
Viewing Angle	2 θ 1/2	/	6	/	deg	IF= 20 mA
Peak Wavelength	λ p	/	611	/	nm	IF= 20 mA
Dominant Wavelength	λ d	/	605	/	nm	IF= 20 mA
Spectrum Radiation Bandwidth	△ λ	/	17	/	nm	IF= 20 mA
Forward Voltage	VF	1.7	2.0	2.4	V	IF= 20 mA
Reverse Current	IR	/	/	10	μ A	VR= 5 V









# EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : CDLE-136-069 REV.: 2

10.0mm Round Type LED Lamps

PART NO. : 1363-2UYOC/S530-A4 ECN :                      Page: 3/4

## ■ Typical Electro-Optical Characteristic Curves:





### 10.0mm Round Type LED Lamps

PART NO. : 1363-2UYOC/S530-A4 ECN : Page: 4/4

- Reliability test items and conditions:

NO	Item	Test Conditions	Test Hours/Cycle		Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	5 SEC	76 PCS	0/1
2	Temperature Cycle	H : +85°C 30min ∫ 5 min L : -55°C 30min	50 CYCLES	76 PCS	0/1
3	Thermal Shock	H : +100°C 5min ∫ 10 sec L : -10°C 5min	50 CYCLES	76 PCS	0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -55°C	1000 HRS	76 PCS	0/1
6	DC Operating Life	TEMP : 25°C  If = 20mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85°C / 85% RH	1000 HRS	76 PCS	0/1