

N-Channel Silicon Junction Field-Effect Transistor**• Low-Noise, High Gain Amplifier****Absolute maximum ratings = T_A at 25°C**

Reverse Gate Source Voltage & Gate Drain Voltage	- 20 V
Continuous Forward Gate Current	10 mA
Continuous Device Power Dissipation	300 mW
Power Derating	2 mW/°C
Storage Temperature Range	- 65°C to 200°C

At 25°C free air temperature:

Static Electrical Characteristics

	IF1801		Process NJ1800DL		
	Min	Max	Unit	Test Conditions	
Gate Source Breakdown Voltage	$V_{(BR)GSS}$	- 20	V	$I_G = - 1 \mu A$, $V_{DS} = \emptyset V$	
Gate Reverse Current	I_{GSS}		nA	$V_{GS} = - 10V$, $V_{DS} = \emptyset V$	
Gate Source Cutoff Voltage	$V_{GS(OFF)}$	- 0.35	- 2	V	$V_{DS} = 10V$, $I_D = 0.5 nA$
Drain Saturation Current (Pulsed)	I_{DSS}	30	mA	$V_{DS} = 10V$, $V_{GS} = \emptyset V$	

Dynamic Electrical Characteristics

Common Source Forward Transconductance	g_{fs}	50		mS	$V_{DS} = 10V$, $I_D = 5 mA$	f = 1 kHz
Common Source Input Capacitance	C_{iss}		100	pF	$V_{DS} = 10V$, $I_D = 5 mA$	f = 1 MHz
Common Source Reverse Transfer Capacitance	C_{rss}		50	pF	$V_{DS} = 10V$, $I_D = 5 mA$	f = 1 MHz

Typ

Equivalent Short Circuit Input Noise Voltage	\bar{e}_N	0.5	nV/ \sqrt{Hz}	$V_{DG} = 4V$, $I_D = 5 mA$	f = 1 kHz
--	-------------	-----	-----------------	------------------------------	-----------

TO-52 Package

Dimensions in Inches (mm)

Pin Configuration

1 Source, 2 Drain, 3 Gate & Case

