

International  
**IR** Rectifier

## ST730C..L SERIES

PHASE CONTROL THYRISTORS

Hockey Puk Version


### Features

- Center amplifying gate
- Metal case with ceramic insulator
- International standard case TO-200AC (B-PUK)

990A

### Typical Applications

- DC motor controls
- Controlled DC power supplies
- AC controllers



case style TO-200AC (B-PUK)

### Major Ratings and Characteristics

Parameters	ST730C..L	Units
$I_{T(AV)}$	990	A
@ $T_{hs}$	55	°C
$I_{T(RMS)}$	2000	A
@ $T_{hs}$	25	°C
$I_{TSM}$	@ 50Hz	17800 A
	@ 60Hz	18700 A
$I^2t$	@ 50Hz	1591 KA <sup>2</sup> s
	@ 60Hz	1452 KA <sup>2</sup> s
$V_{DRM}/V_{RRM}$	800 to 2000	V
$t_q$ typical	150	μs
$T_J$	- 40 to 125	°C

## ST730C..L Series

Bulletin I25191 rev. D 04/03

International  
**IR** Rectifier

### ELECTRICAL SPECIFICATIONS

#### Voltage Ratings

Type number	Voltage Code	$V_{DRM}/V_{RRM}$ , max. repetitive peak and off-state voltage V	$V_{RSM}$ , maximum non-repetitive peak voltage V	$I_{DRM}/I_{RRM}$ max. @ $T_J = T_J \text{ max}$ mA
ST730C..L	08	800	900	80
	12	1200	1300	
	14	1400	1500	
	16	1600	1700	
	18	1800	1900	
	20	2000	2100	

#### On-state Conduction

Parameter	ST730C..L	Units	Conditions
$I_{T(AV)}$ Max. average on-state current @ Heatsink temperature	990 (375)	A	180° conduction, half sine wave double side (single side) cooled
	55 (85)	°C	
$I_{T(RMS)}$ Max. RMS on-state current	2000	A	DC @ 25°C heatsink temperature double side cooled
$I_{TSM}$ Max. peak, one-cycle non-repetitive surge current	17800		t = 10ms No voltage
	18700		t = 8.3ms reapplied
	15000		t = 10ms 100% $V_{RRM}$
	15700		t = 8.3ms reapplied
$I^2t$ Maximum $I^2t$ for fusing	1591	KA <sup>2</sup> s	t = 10ms No voltage
	1452		t = 8.3ms reapplied
	1125		t = 10ms 100% $V_{RRM}$
	1027		t = 8.3ms reapplied
$I^2\sqrt{t}$ Maximum $I^2\sqrt{t}$ for fusing	15910	KA <sup>2</sup> √s	t = 0.1 to 10ms, no voltage reapplied
$V_{T(TO)1}$ Low level value of threshold voltage	0.98	V	(16.7% $\times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)}$ ), $T_J = T_J \text{ max}$ .
$V_{T(TO)2}$ High level value of threshold voltage	1.12		( $I > \pi \times I_{T(AV)}$ ), $T_J = T_J \text{ max}$ .
$r_{t1}$ Low level value of on-state slope resistance	0.32	mΩ	(16.7% $\times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)}$ ), $T_J = T_J \text{ max}$ .
$r_{t2}$ High level value of on-state slope resistance	0.27		( $I > \pi \times I_{T(AV)}$ ), $T_J = T_J \text{ max}$ .
$V_{TM}$ Max. on-state voltage	1.62	V	$I_{pk} = 2000A$ , $T_J = T_J \text{ max}$ , $t_p = 10ms$ sine pulse
$I_H$ Maximum holding current	600	mA	$T_J = 25^\circ C$ , anode supply 12V resistive load
$I_L$ Typical latching current	1000		

#### Switching

Parameter	ST730C..L	Units	Conditions
$di/dt$ Max. non-repetitive rate of rise of turned-on current	1000	A/μs	Gate drive 20V, 20Ω, $t_r \leq 1\mu s$ $T_J = T_J \text{ max}$ , anode voltage $\leq 80\% V_{DRM}$
$t_d$ Typical delay time	1.0	μs	Gate current 1A, $di_g/dt = 1A/\mu s$ $V_d = 0.67\% V_{DRM}$ , $T_J = 25^\circ C$
$t_q$ Typical turn-off time	150		$I_{TM} = 750A$ , $T_J = T_J \text{ max}$ , $di/dt = 60A/\mu s$ , $V_R = 50V$ $dv/dt = 20V/\mu s$ , Gate 0V 100Ω, $t_p = 500\mu s$

### Blocking

Parameter	ST730C..L	Units	Conditions
$dv/dt$ Maximum critical rate of rise of off-state voltage	500	V/ $\mu$ s	$T_J = T_J \text{ max. linear to } 80\% \text{ rated } V_{DRM}$
$I_{DRM}$ $I_{RRM}$ Max. peak reverse and off-state leakage current	80	mA	$T_J = T_J \text{ max, rated } V_{DRM}/V_{RRM} \text{ applied}$

### Triggering

Parameter	ST730C..L	Units	Conditions
$P_{GM}$ Maximum peak gate power	10.0	W	$T_J = T_J \text{ max, } t_p \leq 5\text{ms}$
$P_{G(AV)}$ Maximum average gate power	2.0		$T_J = T_J \text{ max, } f = 50\text{Hz, } d\% = 50$
$I_{GM}$ Max. peak positive gate current	3.0	A	$T_J = T_J \text{ max, } t_p \leq 5\text{ms}$
$+V_{GM}$ Maximum peak positive gate voltage	20	V	$T_J = T_J \text{ max, } t_p \leq 5\text{ms}$
$-V_{GM}$ Maximum peak negative gate voltage	5.0		
$I_{GT}$ DC gate current required to trigger	TYP.	MAX.	$T_J = -40^\circ\text{C}$ $T_J = 25^\circ\text{C}$ $T_J = 125^\circ\text{C}$ Max. required gate trigger/ current/ voltage are the lowest value which will trigger all units 12V anode-to-cathode applied
	200	-	
	100	200	
	50	-	
$V_{GT}$ DC gate voltage required to trigger	2.5	-	$T_J = -40^\circ\text{C}$
	1.8	3.0	$T_J = 25^\circ\text{C}$
	1.1	-	$T_J = 125^\circ\text{C}$
$I_{GD}$ DC gate current not to trigger	10	mA	$T_J = T_J \text{ max}$ Max. gate current/voltage not to trigger is the max. value which will not trigger any unit with rated $V_{DRM}$ anode-to-cathode applied
$V_{GD}$ DC gate voltage not to trigger	0.25	V	

### Thermal and Mechanical Specification

Parameter	ST730C..L	Units	Conditions
$T_J$ Max. operating temperature range	-40 to 125	$^\circ\text{C}$	
$T_{stg}$ Max. storage temperature range	-40 to 150		
$R_{thJ-hs}$ Max. thermal resistance, junction to heatsink	0.073 0.031	K/W	DC operation single side cooled DC operation double side cooled
$R_{thC-hs}$ Max. thermal resistance, case to heatsink	0.011 0.006	K/W	DC operation single side cooled DC operation double side cooled
F Mounting force, $\pm 10\%$	14700 (1500)	N (Kg)	
wt Approximate weight	255	g	
Case style	TO-200AC (B-PUK)		See Outline Table

ST730C..L Series

Bulletin I25191 rev. D 04/03

$\Delta R_{thJ-hs}$  Conduction

(The following table shows the increment of thermal resistance  $R_{thJ-hs}$  when devices operate at different conduction angles than DC)

Conduction angle	Sinusoidal conduction		Rectangular conduction		Units	Conditions
	Single Side	Double Side	Single Side	Double Side		
180°	0.009	0.009	0.006	0.006	K/W	$T_J = T_{J \text{ max.}}$
120°	0.011	0.011	0.010	0.011		
90°	0.014	0.014	0.015	0.015		
60°	0.020	0.020	0.021	0.021		
30°	0.036	0.036	0.036	0.036		

Ordering Information Table

Device Code

ST	73	0	C	20	L	1	
1	2	3	4	5	6	7	8

1

 - Thyristor

2

 - Essential part number

3

 - 0 = Converter grade

4

 - C = Ceramic Puk

5

 - Voltage code: Code x 100 =  $V_{RRM}$  (See Voltage Rating Table)

6

 - L = Puk Case TO-200AC (B-PUK)

7

 - 0 = Eyelet terminals (Gate and Auxiliary Cathode Unsoldered Leads)  
1 = Fast-on terminals (Gate and Auxiliary Cathode Unsoldered Leads)  
2 = Eyelet terminals (Gate and Auxiliary Cathode Soldered Leads)  
3 = Fast-on terminals (Gate and Auxiliary Cathode Soldered Leads)

8

 - Critical dv/dt: None = 500V/ $\mu$ sec (Standard selection)  
L = 1000V/ $\mu$ sec (Special selection)

Outline Table





Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics

## ST730C..L Series

Bulletin I25191 rev. D 04/03

International  
**IRF** Rectifier




Fig. 3 - Current Ratings Characteristics




Fig. 4 - Current Ratings Characteristics




Fig. 5 - On-state Power Loss Characteristics




Fig. 6 - On-state Power Loss Characteristics




Fig. 7 - Maximum Non-Repetitive Surge Current  
Single and Double Side Cooled




Fig. 8 - Maximum Non-Repetitive Surge Current  
Single and Double Side Cooled




Fig. 9 - On-state Voltage Drop Characteristics




Fig. 10 - Thermal Impedance  $Z_{thJ-hs}$  Characteristics




Fig. 11 - Gate Characteristics

## **ST730C..L Series**

Bulletin I25191 rev. D 04/03

International  
**IOR** Rectifier

Data and specifications subject to change without notice.  
This product has been designed and qualified for Industrial Level.  
Qualification Standards can be found on IR's Web site.

International  
**IOR** Rectifier

**IR WORLD HEADQUARTERS:** 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105  
TAC Fax: (310) 252-7309  
Visit us at [www.irf.com](http://www.irf.com) for sales contact information. 04 /03