

Ledtech DUAL DIGIT DISPLAY

0.5" DUAL DIGIT DISPLAY Electrical/Optical Characteristics at T_A=25°C & I_F=20mA

CHIP COLOR	0.5 inch DUAL DIGIT DUPLEX DRIVE		0.5 inch DUAL DIGIT DIRECT DRIVE		λ p (nm)	V _F (V)	I _V (mcd)	
	COMMON ANODE	COMMON CATHODE	COMMON ANODE	COMMON CATHODE	TYP.	TYP.	MIN.	TYP.
GREEN	LD5022-11	LE5022-11	LA5022-11	LC5022-11	572	2.1	3.9	6.5
YELLOW	LD5032-11	LE5032-11	LA5032-11	LC5032-11	589	2.1	3.1	5.2
ORANGE	LD5042-11	LE5042-11	LA5042-11	LC5042-11	630	2.1	4.5	7.4
ORANGE	LD5042R-11	LE5042R-11	LA5042R-11	LC5042R-11	630	2.1	4.5	7.4
RED	LD5072-11-M1	LE5072-11-M1	LA5072- 11-M1	LC5072- 11-M1	660	1.7	10.4	17.3
RED	LD5052-11	LE5052-11	LA5052- 11	LC5052-11	700	2.1	1.1	1.8

LD50X2-11

COMMON ANODE

PIN


NO.	FUNCTION
1. CATHODE	D
2. CATHODE	DP
3. CATHODE	E
4. CATHODE	C
5. COMMON	ANODE
(DIGIT 2)	
6. CATHODE	B
7. CATHODE	A
8. CATHODE	F
9. CATHODE	G
10. COMMON	ANODE
(DIGIT 1)	

LE50X2-11

COMMON CATHODE

PIN

NO.	FUNCTION
1. ANODE	D
2. ANODE	DP
3. ANODE	E
4. ANODE	C
5. COMMON	CATHODE
(DIGIT 2)	
6. ANODE	B
7. ANODE	A
8. ANODE	F
9. ANODE	G
10. COMMON	CATHODE
(DIGIT 1)	



LA50X2-11

COMMON ANODE

PIN


NO.	FUNCTION
1. CATHODE	E (DIGIT 1)
2. CATHODE	D (DIGIT 1)
3. CATHODE	C (DIGIT 1)
4. CATHODE	DP (DIGIT 1)
5. CATHODE	E (DIGIT 2)
6. CATHODE	D (DIGIT 2)
7. CATHODE	G (DIGIT 2)
8. CATHODE	C (DIGIT 2)
9. CATHODE	DP (DIGIT 2)
10. CATHODE	B (DIGIT 2)
11. CATHODE	A (DIGIT 2)
12. CATHODE	F (DIGIT 2)
13. COMMON	ANODE
(DIGIT 2)	
14. COMMON	ANODE
(DIGIT 1)	
15. CATHODE	B (DIGIT 1)
16. CATHODE	A (DIGIT 1)
17. CATHODE	G (DIGIT 1)
18. CATHODE	F (DIGIT 1)

LC50X2-11

COMMON CATHODE

PIN

NO.	FUNCTION
1. ANODE	E (DIGIT 1)
2. ANODE	D (DIGIT 1)
3. ANODE	C (DIGIT 1)
4. ANODE	DP (DIGIT 1)
5. ANODE	E (DIGIT 2)
6. ANODE	D (DIGIT 2)
7. ANODE	G (DIGIT 2)
8. ANODE	C (DIGIT 2)
9. ANODE	DP (DIGIT 2)
10. ANODE	B (DIGIT 2)
11. ANODE	A (DIGIT 2)
12. ANODE	F (DIGIT 2)
13. COMMON	CATHODE
(DIGIT 2)	
14. COMMON	CATHODE
(DIGIT 1)	
15. ANODE	B (DIGIT 1)
16. ANODE	A (DIGIT 1)
17. ANODE	G (DIGIT 1)
18. ANODE	F (DIGIT 1)



NOTES : 1.ALL DIMENSIONS ARE IN mm, TOLERANCE IS ±0.25mm (0.01") UNLESS OTHERWISE NOTED.

2.THE SLOPE ANGLE OF ANY PIN MAY BE ±5° MAX.