

G12™-p bd4f5fs60ls33


4 mA, 60 MHz, 5-Volt Tolerant, Fail-Safe I/O Buffer

Datasheet



The bd4f5fs60ls33 bidirectional buffer cell ([Figure 1](#)) provides up to 60 MHz off-chip input/output (I/O) signaling for application-specific integrated circuit (ASIC) chips implemented in the LSI Logic G12™-p 0.13 μm process technology. One application of the bd4f5fs60ls33 buffer is as a clock driver.

Figure 1 **bd4f5fs60ls33 Block Diagram**



Features and Benefits

- 60 MHz, 3.3 V I/O operation
- 5-Volt tolerant
- Fail-safe at high voltages
- Feedthrough protection
- 20 μA maximum leakage current
- Minimum 4 mA current drive into a 40 pF load at 60 MHz
- 1.8 V internal signaling for reduced power consumption
- Uses one standard I/O slot

General Description

The bd4f5fs60ls33 bidirectional I/O buffer contains a totem-pole type driver, a receiver, and test circuitry. Included level translation circuitry enables the driver to receive 1.8 V level signals from the ASIC circuitry

and produce 3.3 V level output at the I/O pad. Similarly, the receiver receives off-chip input at 3.3 volts and translates it to 1.8 volts for the internal ASIC application. Built-in NAND-tree logic gates and IDDTN control for IDDQ leakage testing enable use of the standard LSI Logic test methodology.

The buffer is 5-volt tolerant. Although the off-chip I/O signaling normally operates at 3.3 V, external circuitry may cause higher voltages, typically upwards of 5 V, to appear at the chip I/O pad. Circuit and process techniques ensure that such DC or transient voltages do not damage the buffer circuitry.

In the absence of a V_{DD} supply, the buffer is fail-safe and protected against voltage feedthrough. With high voltage applied to the chip I/O pad, the buffer can survive without degradation for up to ten years. Furthermore, with a low, maximum 20 μ A leakage current, the high voltage can not power up the ASIC through voltage feedthrough.

The following sections describe the bd4f5fs60ls33 buffer, which adheres to the general specifications in [Table 1](#).

Table 1 General Specifications

Symbol	Parameter	Condition	Min.	Typ.	Max.	Unit
V_{DD}	Supply voltage		2.97	3.3	3.63	V
T_j	Junction temperature		0	–	125	°C
ESD	Electrostatic discharge, human body model (HBM)	MIL-STD-883C, Method 3015.7 100 pF @1.5 K Ω	2000	–	–	V
	Electrostatic discharge, charged device model (CDM)	ESD DS5.3.1-1996	500	–	–	V

The final section, “[System Design Guidelines](#)”, provides layout guidelines to ensure good signal integrity for applications using the noise-sensitive, high-speed cells.

Signal Descriptions

[Table 2](#) describes the bd4f5fs60ls33 connections.

Table 2 bd4f5fs60ls33 Connections

Signal	Direction	Description
A	IN	Data input to driver from ASIC circuitry
EN	IN	0 = Normal mode 1 = Disable driver
IDDTN	IN	0 = Power down entire cell ¹ 1 = Normal mode
PI	IN	NAND-tree parametric test input
TN	IN	0 = Disable driver 1 = Normal mode
IO	IN/OUT	Input/output pad
PO	OUT	NAND-tree parametric test output
Z	OUT	Receiver buffer output to ASIC circuitry

1. Used for production IDDQ leakage test

Driver

The following sections describe the driver side of the I/O buffer.

Truth Table

[Table 3](#) describes the bd4f5fs60ls33 driver behavior.

Table 3 Driver Truth Table

IDDTN	A	TN	EN	IO
0 ¹	X ²	X	X	High Impedance
1	X	X	1	High Impedance
1	X	0	X	High Impedance
1	0	1	0	0
1	1	1	0	1

1. Factory IDDQ test setting
2. Don't care state, X = 0 or 1

Driver Specifications

DC Characteristics

Table 4 describes the bd4f5fs60ls33 driver DC characteristics.

Table 4 Driver DC Characteristics¹

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
V_{OL}	Output, LOW	$I_{OL} = 4 \text{ mA}$	–	–	0.4	V
V_{OH}	Output, HIGH	$I_{OH} = -4 \text{ mA}$ $V_{DD} = 3.135 \text{ V}$	2.4	–	–	V
I_{OL}	Sink current	$V_{OL} = 0.4 \text{ V}$ maximum	4	–	–	mA
I_{OH}	Source current	$V_{OH} = 2.4 \text{ V}$ minimum	–	–	–4	mA
I_{OZ}	3-States leakage current	$0 \leq V_{PAD} \leq 5.5 \text{ V}$, $V_{DD} = 3.3 \text{ V} \pm 10\%$	–	–	20	μA
I_{LU}	Latchup current	$-2 \text{ V} < V_{PAD} < +8 \text{ V}$	–	–	± 100	mA

1. Values apply over all voltage, temperature, and process conditions.

Driver Slew Rate

In the rise/fall test, the driver drives a signal across a 40 pF load capacitor (Figure 2). Table 5 shows the observed slew rate across the load capacitor measured from 0.6 V to 2.2 V.

Figure 2 Rise/Fall Test Circuit




Table 5 Driver Rise/Fall Slew Rate

Min.	Typ.	Max.	Unit
500	880	1500	mV/ns

Receiver

The following sections describe the receiver side of the I/O buffer.

Truth Table

Table 6 describes the bd4f5fs60ls33 receiver behavior.

Table 6 Receiver Truth Table

Inputs			Outputs	
IDDTN	IO	PI	Z	PO
0 ¹	High Impedance	1	1	0
1	0	0	0	1
1	1	0	1	1
1	1	1	1	0

1. Factory IDDQ test setting

Receiver Specifications

Table 7 describes the bd4f5fs60ls33 receiver DC characteristics.

Table 7 Receiver DC Characteristics¹

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
V _{IL}	Threshold, HIGH-to-LOW		1.0	–	1.50	V
V _{IH}	Threshold, LOW-to-HIGH		1.50	–	2.0	V
V _{TH} –V _{TL}	Hysteresis		320	–	–	mV
I _{LU}	Latch-up current	–2 V < V _{PAD} < +8 V	–	–	±100	mA

1. Values apply over all voltage, temperature, and process conditions

System Design Guidelines

To ensure good system-level operation, LSI Logic provides the following guidelines for placing the `bd4f5fs60ls33` in the ASIC and for supplying power.

Placement

The `bd4f5fs60ls33` cell requires placement on the I/O ring ([Table 8](#)) using one I/O slot.

Table 8 `bd4f5fs60ls33` Dimensions on the I/O Ring

Width Along the I/O Ring	Length into the Chip
45.36 μm	371.01 μm

For correct placement of the `bd4f5fs60ls33` cell, adhere to the following guidelines:

- A `bd4f5fs60ls33` cell may adjoin another `bd4f5fs60ls33` cell or a `d4f5fsls33`, `bd4puf5fsls33`, or `bd4puodf5fsls33` cell.
- Separate the `bd4f5fs60ls33` cell from any other type of I/O function by at least one I/O slot to avoid N-channel to P-channel design rule violations. If possible, use a VDD or VSS pad for the separation.
- Because its length exceeds the length of other standard I/O functions, the `bd4f5fs60ls33` cell may not use a corner I/O slot.

Power

For best system-level performance, adhere to the following power guidelines:

- Use one power/ground pad pair for every four I/O cells.
- Place an I/O cell no more than four slots away from a power pad and no more than four slots away from a ground pad.

Notes

Sales Offices and Design Resource Centers

LSI Logic Corporation Corporate Headquarters Tel: 408.433.8000 Fax: 408.433.8989	Illinois Oakbrook Terrace Tel: 630.954.2234 Fax: 630.954.2235	Texas Austin Tel: 512.388.7294 Fax: 512.388.4171	Korea Seoul LSI Logic Corporation of Korea Ltd Tel: 82.2.528.3400 Fax: 82.2.528.2250
NORTH AMERICA	Kentucky Bowling Green Tel: 270.793.0010 Fax: 270.793.0040	Plano ◆ Tel: 972.244.5000 Fax: 972.244.5001	The Netherlands Eindhoven LSI Logic Europe Ltd Tel: 31.40.265.3580 Fax: 31.40.296.2109
California Irvine ◆ Tel: 949.809.4600 Fax: 949.809.4444	Maryland Bethesda Tel: 301.897.5800 Fax: 301.897.8389	Houston Tel: 281.379.7800 Fax: 281.379.7818	Singapore Singapore LSI Logic Pte Ltd Tel: 65.334.9061 Fax: 65.334.4749
Pleasanton Design Center Tel: 925.730.8800 Fax: 925.730.8700	Massachusetts Waltham ◆ Tel: 781.890.0180 Fax: 781.890.6158	Canada Ontario Ottawa ◆ Tel: 613.592.1263 Fax: 613.592.3253	Sweden Stockholm LSI Logic AB ◆ Tel: 46.8.444.15.00 Fax: 46.8.750.66.47
San Diego Tel: 858.467.6981 Fax: 858.496.0548	Burlington - Mint Technology Tel: 781.685.3800 Fax: 781.685.3801	INTERNATIONAL	Taiwan Taipei LSI Logic Asia, Inc. Taiwan Branch Tel: 886.2.2718.7828 Fax: 886.2.2718.8869
Silicon Valley ◆ Tel: 408.433.8000 Fax: 408.954.3353	Minnesota Minneapolis ◆ Tel: 612.921.8300 Fax: 612.921.8399	France Paris LSI Logic S.A. Immeuble Europa ◆ Tel: 33.1.34.63.13.13 Fax: 33.1.34.63.13.19	United Kingdom Bracknell LSI Logic Europe Ltd ◆ Tel: 44.1344.426544 Fax: 44.1344.481039
Wireless Design Center Tel: 858.350.5560 Fax: 858.350.0171	New Jersey Red Bank Tel: 732.933.2656 Fax: 732.933.2643	Germany Munich LSI Logic GmbH ◆ Tel: 49.89.4.58.33.0 Fax: 49.89.4.58.33.108	◆ Sales Offices with Design Resource Centers
Colorado Boulder ◆ Tel: 303.447.3800 Fax: 303.541.0641	Cherry Hill - Mint Technology Tel: 856.489.5530 Fax: 856.489.5531	Stuttgart ◆ Tel: 49.711.13.96.90 Fax: 49.711.86.61.428	
Colorado Springs Tel: 719.533.7000 Fax: 719.533.7020	New York Fairport Tel: 716.218.0020 Fax: 716.218.9010	Italy Milan LSI Logic S.P.A. ◆ Tel: 39.039.687371 Fax: 39.039.6057867	
Fort Collins Tel: 970.223.5100 Fax: 970.206.5549	North Carolina Raleigh Tel: 919.785.4520 Fax: 919.783.8909	Japan Tokyo LSI Logic K.K. ◆ Tel: 81.3.5463.7821 Fax: 81.3.5463.7820	
Florida Boca Raton Tel: 561.989.3236 Fax: 561.989.3237	Oregon Beaverton Tel: 503.645.0589 Fax: 503.645.6612	Osaka ◆ Tel: 81.6.947.5281 Fax: 81.6.947.5287	
Georgia Alpharetta Tel: 770.753.6146 Fax: 770.753.6147			

To receive product literature, visit us at <http://www.lsilogic.com>

ISO 9000 Certified

The LSI Logic logo design is a registered trademark of LSI Logic Corporation. All other brand and product names may be trademarks of their respective companies.

LSI Logic Corporation reserves the right to make changes to any products and services herein at any time without notice. LSI Logic does not assume any responsibility or liability arising out of the application or use of any product or service described herein, except as expressly agreed to in writing by LSI Logic; nor does the purchase, lease, or use of a product or service from LSI Logic convey a license under any patent rights, copyrights, trademark rights, or any other of the intellectual property rights of LSI Logic or of third parties.