





This socket is equipped with contacts combining two connection techniques: up to three-level wrapping plus PCB soldering

Also suitable for use as an interconnect socket with intermediate wire-wrap connections. Custom lengths on request


Insertion characteristics:  
4-finger standard



Platings	Sleeve 	Clip 	Pin 
93	5 µm Sn Pb	0.75 µm Au	

#### Ordering information

For complete part number see Order Codes list below

No. of poles	Order Codes				Insulator dimensions			
	Plating 93 <b>B</b>	Plating 93 <b>B</b>	Plating 93 <b>B</b>			A	B	C
	L = 5.9 1 Level	L = 8.9 2 Level	L = 11.9 3 Level		See page 50			
10	126-93-210-41-001	126-93-210-41-002	126-93-210-41-003		Fig. 1	12.6	5.08	7.6
4	126-93-304-41-001	126-93-304-41-002	126-93-304-41-003		Fig. 2	5.0	7.62	10.1
6	126-93-306-41-001	126-93-306-41-002	126-93-306-41-003		Fig. 3	7.6	7.62	10.1
8	126-93-308-41-001	126-93-308-41-002	126-93-308-41-003		Fig. 4	10.1	7.62	10.1
10	126-93-310-41-001	126-93-310-41-002	126-93-310-41-003		Fig. 5	12.6	7.62	10.1
12	126-93-312-41-001	126-93-312-41-002	126-93-312-41-003		Fig. 5a	15.2	7.62	10.1
14	126-93-314-41-001	126-93-314-41-002	126-93-314-41-003		Fig. 6	17.7	7.62	10.1
16	126-93-316-41-001	126-93-316-41-002	126-93-316-41-003		Fig. 7	20.3	7.62	10.1
18	126-93-318-41-001	126-93-318-41-002	126-93-318-41-003		Fig. 8	22.8	7.62	10.1
20	126-93-320-41-001	126-93-320-41-002	126-93-320-41-003		Fig. 9	25.3	7.62	10.1
22	126-93-322-41-001	126-93-322-41-002	126-93-322-41-003		Fig. 10	27.8	7.62	10.1
24	126-93-324-41-001	126-93-324-41-002	126-93-324-41-003		Fig. 11	30.4	7.62	10.1
28	126-93-328-41-001	126-93-328-41-002	126-93-328-41-003		Fig. 12	35.5	7.62	10.1
20	126-93-420-41-001	126-93-420-41-002	126-93-420-41-003		Fig. 12a	25.3	10.16	12.6
22	126-93-422-41-001	126-93-422-41-002	126-93-422-41-003		Fig. 13	27.8	10.16	12.6
24	126-93-424-41-001	126-93-424-41-002	126-93-424-41-003		Fig. 14	30.4	10.16	12.6
28	126-93-428-41-001	126-93-428-41-002	126-93-428-41-003		Fig. 15	35.5	10.16	12.6
32	126-93-432-41-001	126-93-432-41-002	126-93-432-41-003		Fig. 16	40.6	10.16	12.6
10	126-93-610-41-001	126-93-610-41-002	126-93-610-41-003		Fig. 16a	12.6	15.24	17.7
24	126-93-624-41-001	126-93-624-41-002	126-93-624-41-003		Fig. 17	30.4	15.24	17.7
28	126-93-628-41-001	126-93-628-41-002	126-93-628-41-003		Fig. 18	35.5	15.24	17.7
32	126-93-632-41-001	126-93-632-41-002	126-93-632-41-003		Fig. 19	40.6	15.24	17.7
36	126-93-636-41-001	126-93-636-41-002	126-93-636-41-003		Fig. 20	45.7	15.24	17.7
40	126-93-640-41-001	126-93-640-41-002	126-93-640-41-003		Fig. 21	50.6	15.24	17.7
42	126-93-642-41-001	126-93-642-41-002	126-93-642-41-003		Fig. 22	53.2	15.24	17.7
48	126-93-648-41-001	126-93-648-41-002	126-93-648-41-003		Fig. 23	60.9	15.24	17.7
50	126-93-650-41-001	126-93-650-41-002	126-93-650-41-003		Fig. 24	63.4	15.24	17.7
52	126-93-652-41-001	126-93-652-41-002	126-93-652-41-003		Fig. 25	65.9	15.24	17.7
50	126-93-950-41-001	126-93-950-41-002	126-93-950-41-003		Fig. 26	63.4	22.86	25.3
52	126-93-952-41-001	126-93-952-41-002	126-93-952-41-003		Fig. 27	65.9	22.86	25.3
64	126-93-964-41-001	126-93-964-41-002	126-93-964-41-003		Fig. 28	81.1	22.86	25.3