

UTC HE8550 PNP EPITAXIAL SILIC ON TRANSISTOR


LOW VOLTAGE HIGH CURRENT SMALL SIGNAL PNP TRANSISTOR

DESCRIPTION

The UTC HE8550 is a low voltage high current small signal PNP transistor, designed for Class B push-pull 2W audio amplifier for portable radio and general purpose applications.

FEATURES

- *Collector current up to 1.5A
- *Collector-Emitter voltage up to 25 V
- *Complimentary to UTC HE8050



1:EMITTER 2:COLLECTOR 3:BASE

ABSOLUTE MAXIMUM RATINGS (Ta=25°C, unless otherwise specified)

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	V _{CB0}	-40	V
Collector-Emitter Voltage	V _{CE0}	-25	V
Emitter-Base Voltage	V _{EB0}	-6	V
Collector Dissipation(Ta=25°C)	P _c	1	W
Collector Current	I _c	-1.5	A
Junction Temperature	T _j	150	°C
Storage Temperature	T _{STG}	-65 ~ +150	°C

ELECTRICAL CHARACTERISTICS (Tj=25°C, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector-Base Breakdown Voltage	BV _{CB0}	I _c =-100μA, I _E =0	-40			V
Collector-Emitter Breakdown Voltage	BV _{CE0}	I _c =-2mA, I _B =0	-25			V
Emitter-Base Breakdown Voltage	BV _{EB0}	I _E =-100μA, I _c =0	-6			V
Collector Cut-Off Current	I _{CB0}	V _{CB} =-35V, I _E =0			-100	nA
Emitter Cut-Off Current	I _{EB0}	V _{EB} =-6V, I _c =0			-100	nA
DC Current Gain(note)	h _{FE1}	V _{CE} =-1V, I _c =-5mA	45	170		
	h _{FE2}	V _{CE} =-1V, I _c =-100mA	85	160	500	
	h _{FE3}	V _{CE} =-1V, I _c =-800mA	40	80		
Collector-Emitter Saturation Voltage	V _{CE(sat)}	I _c =-800mA, I _B =-80mA		-0.28	-0.5	V
Base-Emitter Saturation Voltage	V _{BE(sat)}	I _c =-800mA, I _B =-80mA		-0.98	-1.2	V
Base-Emitter Voltage	V _{BE}	V _{CE} =-1V, I _c =-10mA		-0.66	-1.0	V
Current Gain Bandwidth Product	f _T	V _{CE} =-10V, I _c =-50mA	100	190		MHz
Output Capacitance	C _{ob}	V _{CB} =-10V, I _E =0 f=1MHz		9.0		pF

UTC HE8550 PNP EPITAXIAL SILIC ON TRANSISTOR

CLASSIFICATION OF hFE

RANK	C	D	E
RANGE	120-200	160-300	250-500

TYPICAL PERFORMANCE CHARACTERISTICS

Fig.1 Static characteristics




Fig.2 DC current Gain




Fig.3 Base-Emitter on Voltage




Fig.4 Saturation voltage




Fig.5 Current gain-bandwidth product





Fig.6 Collector output Capacitance



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.