

Infrared Emitting Diode

Module No.: IE-0520HT


1. General Description:

IE-0520HT is a high output power and high speed GaAlAs infrared light emitting diode, mounted in a clear epoxy end looking package. It emits medium band of radiation peaking at 880nm.

2. Features

- Standard package (Ø5mm)
- Medium beam angle ($\pm 20^\circ$)
- Capable of pulse operation
- High output power
- Good Linearity

Dimensions



3. Absolute Maximum Ratings

($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Ratings	Unit
Forward Current	I_F	100	mA
Pulse Forward current *1	I_{FP}	1	A
Reverse Voltage	V_R	5	V
Power Dissipation	P_D	95	mW
Operating Temperature	T_{opr}	$-20 \sim +85$	$^\circ\text{C}$
Storage Temperature	T_{stg}	$-25 \sim +90$	$^\circ\text{C}$
Soldering Temperature *2	T_{sol}	260	$^\circ\text{C}$



*1 Pulse width $\leq 100\mu\text{sec}$. Duty ratio = 0.01

*2 At the position of 2mm from the bottom of the package within 5 seconds.

4. Electro-optical Characteristics

($T_a = 25^\circ\text{C}$)


Parameter	Symbol	Testing Conditions	Min.	Typ.	Max.	Unit
Forward Voltage	V_F	$I_F = 50\text{mA}$		1.5	1.9	V
Reverse Current	I_R	$V_R = 5\text{V}$			10	μA
Radiant Intensity	P_o	$I_F = 50\text{mA}$	10	25		mW/sr
Terminal Capacitance	C_t	$f = 1\text{MHz}$		20		pF
Half Power Beam Angle	$\Delta\theta$			± 20		deg.
Peak Emission Wavelength	λ_p	$I_F = 100\text{mA}$		880		nm
Spectral bandwidth at 50%	$\Delta\lambda$	$I_F = 100\text{mA}$		80		nm




Infrared Emitting Diode

Module No.: IE-0520HT


Forward Current vs
Forward Voltage




Spectral Distribution




Power Dissipation vs
Ambient Temperature



Relative Output power vs
Ambient Temperature



Relative Power vs
Distance to Detector



Distance to Detector Test Conditions

